

V6 Classic Series Zoom Rooms Version

An all-in-one Zoom Rooms-enabled collaboration board to suit any meeting room.

From huddle rooms to large meeting rooms, MAXHUB IFP V6 Classic Zoom Rooms Version is pre-configured with Zoom Rooms to support Zoom Whiteboard with 10-point multi-touch functionality, annotation and Auto Framing.

The pluggable PC Module makes the IFP V6 Classic easy to upgrade while the color accuracy (smaller than 2 Delta E), 90% NTSC true color, 92° HFOV 48MP 4K UHD camera, 2.1 channel stereo sound and two 10W+20W seam speakers offer an immersive, true-to-life experience.



PC Module	MT61Z	MT61X
Hardware	CPU : Intel i5	CPU : Intel i7
	Memory : 16G	Memory : 16G
	Storage: 256G	Storage: 256G
OS	Windows 10 IOT	Windows 10 IOT
App	Zoom Rooms	Zoom Rooms
	Preconfigured	Preconfigured

*Must order with Zoom Rooms preconfigured PC module.



Professional 4K Display

High Color Accuracy, ΔE≤2
Wide Color Gamut, NTSC 90%




Touch Screen

20 Touch Points,
Minimum Object Recognition - 2mm




Zoom Rooms

Pre-installed Zoom Rooms app
based on windows



Bring Your Own Device

Access to MAXHUB V6 classic's
camera / microphone / speaker
from your laptop



Built-in Camera

48million pixels
Offer the best view in both dark/bright
scene with WDR technology




Built-in Microphone

8 meters of voice pick-up



Built-in Speaker

2.1 Channel
2x 10W + 20W



Energy Saving

Energy Star 8.0 Certified*
(touch display)

Display				
Model / Part No.	C5530	C6530	C7530	C8630
Diagonal Size(inch)	55	65	75	86
Backlight	Direct-lit LED	Direct-lit LED	Direct-lit LED	Direct-lit LED
Panel Technology	IPS	IPS	VA	VA
Aspect Ratio	16 : 9	16 : 9	16 : 9	16 : 9
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Response Time	8ms	8ms	8.5ms	8ms
Brightness(typ)	350cd/m²	350cd/m²	350cd/m²	350cd/m²
Contrast Ratio	1200 : 1	1200 : 1	5000 : 1	4000 : 1
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut(typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape	Landscape	Landscape
Operating Hour	16/7	16/7	16/7	16/7

Dimension&Weight				
Product Dimensions(WxHxD)	1263 x 776 x 88 mm 49.72 x 30.55 x 3.46 inch	1488 x 903 x 88 mm 58.58 x 35.55 x 3.46 inch	1709 x 1026 x 87 mm 73.35 x 44.88 x 8.86 inch	1957.1 x 1160.1 x 100.2 mm 77.05 x 45.67 x 3.94 inch
Shipping Dimensions(WxHxD)	1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch	1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch	2110 x 1283 x 225 mm 83.07 x 50.51 x 6.86 inch
Net Weight (kg /pounds)	26.25kg / 57.87 lbs	36.25kg / 79.92 lbs	48.3kg / 106.48 lbs	59.75kg / 131.73 lbs
Gross Weight (kg /pounds)	34.2kg / 75.40 lbs	46.75kg / 103.07 lbs	62.8kg / 138.45 lbs	77.00kg / 169.76 lbs
Wall Mount(VESA)	400 x 200mm / 15.75 x 7.78inch	600 x 400mm / 23.62 x 15.75inch	800 x 400mm / 31.50x15.75inch	800 x 600mm / 31.50 x 23.62inch
Screws For VESA	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch

POWER				
Power Supply	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Max Power Consumption	300W	350W	400W	400W
Standby	≤0.5W	≤0.5W	≤0.5W	≤0.5W

Touch System	
Touch Sensor	IR Touch
Max Touch Points Supported	20
Accuracy	± 1mm
Object Recognition Range	≥2mm
Glass	Zero parallax , 3mm Angi-glare, Antibacterial
Supported Operating System(Touch Return)	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS

Camera/Audio/Microphone	
Built-in Camera	Yes, Single Camera, 48MP
Camera Features	Auto Frame / Speaker Tracking
Built-in Speakers	2.1 Channel , 2x10W+20W
Microphone Array	8 x Far-field , beam-forming microphone - max 8m range

Connectivity	
Input	HDMI IN x 1 , USB 2.0 x 1, USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x 2
Audio	Audio out x 1
Control	RS232 x 1
PC Module Slot	Yes, 3840 x 2160@60fps
PC Module (must order seperately)	MT61Z / MT61X
Wifi Module	SI06

Environment	
Operating Temperature	0℃~40℃
Storage Temperature	10%~90%RH
Operating Humidity	-20℃~60℃
Storage Humidity	10%~90%RH

What's In The Box				
Standard	Power Cord, 1 x Wifi Adapter, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m 70.9inch)			
Optional (Mobile Stand)				
	ST41B	ST23C	EST09	EST11

MT61Z Specification

General Specifications	
Device Type	Pluggable PC Module
Operating System	Win 10 IOT (64bit)
CPU	Intel Core i5
GPU	Intel UHD Graphics (supports 4K@60Hz)
RAM	16G , DDR4
Internal Storage	256G
Touchscreen Compatibility	Yes
TPM	2.0
Application	Zoom Rooms
Connectivity	
HDMI Out	1 (up to 4K@30fps)
USB 3.0	x3
USB 2.0	x1
RJ45 in	x1
Microphone in	x1
Power	
Power Requirements	18V DC
Power Consumption Maximum	≤ 106.5W
Power Consumption Standby	≤ 1.1W
ENVIRONMENTAL	
Operating Temperature	-10° ~55°
Storage Temperature	-20° ~60°
Operating Humidity	10% - 90%RH
Storage Humidity	10% - 90%RH
Physical Specifications	
Product Dimensions (WxHxD)	202 x 133.5 x 30 mm
Package Dimensions (WxHxD)	314 x 256 x 70 mm
Net Weight	1.325 kg
Gross Weight	1.745 kg
Warranty	
Standard Warranty	3-year Warranty
Support	
For all MAXHUB Products , visit https://www.maxhub.com/en/service	

MT61X Specification

General Specifications	
Device Type	Pluggable PC Module
Operating System	Win 10 IOT (64bit)
CPU	Intel Core i7
GPU	Intel UHD Graphics (supports 4K@60Hz)
RAM	16G , DDR4
Internal Storage	256G
Touchscreen Compatibility	Yes
TPM	2.0
Application	Zoom Rooms
Connectivity	
HDMI Out	1 (up to 4K@30fps)
USB 3.0	x3
USB 2.0	x1
RJ45 in	x1
Microphone in	x1
Power	
Power Requirements	18V DC
Power Consumption Maximum	≤ 106.5W
Power Consumption Standby	≤ 1.1W
ENVIRONMENTAL	
Operating Temperature	-10° ~55°
Storage Temperature	-20° ~60°
Operating Humidity	10% - 90%RH
Storage Humidity	10% - 90%RH
Physical Specifications	
Product Dimensions (WxHxD)	202 x 133.5 x 30 mm
Package Dimensions (WxHxD)	314 x 256 x 70 mm
Net Weight	1.325 kg
Gross Weight	1.745 kg
Warranty	
Standard Warranty	3-year Warranty
Support	
For all MAXHUB Products , visit https://www.maxhub.com/en/service	