

POSIFLEX

Powerful yet Thrifty



PS-3515-G2

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3515-G2 features a 15" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3515-G2

Specification	PS-3515-G2
Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache
System Memory	DDR4 SO-DIMM x 1, max. 16GB
Storage Device	M.2 connector (SATA Signal Only) x 1
TPM	Yes, TPM 2.0
Power Supply	12V/60W
OS Support	Windows 10 IoT LTSC / Windows 11 IoT LTSC

Display & Touch

LCD	15" TFT LCD
Resolution	1024 x 768
Touch	5-wire Resistive touch

I/O & Expansion

Serial Port	4, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	5, USB 3.0 x 2+ USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8 base
OTG USB	N/A
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer
PS/2 Port	1, via optional conversion cable through service window
Audio	Buzzer x 1; Optional internal 2W speaker x 1
Expansion Slot	M.2 slot x 1

Physical Dimension

Dimensions (W x D x H in mm)	372 x 252 x 326
Weight (N. W. in kg)	5.86

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	M.2 WiFi/BT module
------	--------------------

Attachment Options

POS Monitor	Non-touch TFT USB LCD: 7"/9.7"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display
Attachment	MSR; iButton; RFID; Fingerprint Sensor; Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
* The product information and specifications are subject to change without prior notice.
* Please refer to the website for more attachment options.

POSIFLEX

Certifications	      	EN20240402V2
----------------	--	--------------

Authorized Distributor / Reseller

POSIFLEX

Powerful yet Thrifty



PS-3516-G2

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3516-G2 features a 15.6" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3516-G2

Specification

PS-3516-G2

Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache
System Memory	DDR4 SO-DIMM x 1, max. 16GB
TPM	Yes, TPM 2.0
Storage Device	M.2 connector (SATA Signal Only) x 1
Power Supply	12V/60W
OS Support	Windows 10 IoT LTSC / Windows 11 IoT LTSC

Display & Touch

LCD	15.6" TFT LCD
Resolution	1366 x 768
Touch	5-wire Resistive touch

I/O & Expansion

Serial Port	4, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	5, USB 3.0 x 2+ USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
Powered USB Port	Optional 24V x 1 + 12V x 3 via GENB base
OTG USB	N/A
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer
PS/2 Port	1, via optional conversion cable through service window
Audio	Buzzer x 1; Optional internal 2W speaker x 1
Expansion Slot	M.2 slot x 1

Physical Dimension

Dimensions (W x D x H in mm)	372 x 252 x 291.4
Weight (N. W. in kg)	4.7

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	M.2 WiFi/BT module
------	--------------------

Attachment Options

POS Monitor	Non-touch TFT USB LCD: 7"/9.7"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display
Attachment	MSR; iButton; RFID; Fingerprint Sensor; Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice.

* Please refer to the website for more attachment options.

POSIFLEX







Certifications	      	EN20240402V2
----------------	--	--------------

Authorized Distributor / Reseller

CDG | Computer Peripheral and Supplies Ltd.

Computer Peripheral and Supplies Ltd.
244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand

 : facebook.com/cps.co.th
 : Tel. 02-7224040 Ext.9
 : sales.dept@cps.co.th
 : www.cps.co.th

    CPS
Other
 : Tel : (66) 0-2322-9535
 : Fax : (66) 0-2322-7990

 scan here
contact us
Need more information



POSIFLEX

Powerful yet Thrifty



PS-3615-G2

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3615-G2 Series features a 15" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3615-G2

Specification

PS-3615-G2

Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache
System Memory	DDR4 SO-DIMM x 1, max. 16GB
Storage Device	M.2 connector (SATA Signal Only) x 1
TPM	Yes, TPM 2.0
Power Supply	12V/60W
OS Support	Windows 10 IoT LTSC / Windows 11 IoT LTSC

Display & Touch

LCD	15" TFT LCD
Resolution	1024 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)

I/O & Expansion

Serial Port	4, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	5, USB 3.0 x 2+ USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GENB base
OTG USB	N/A
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer
PS/2 Port	1, via optional conversion cable through service window
Audio	Buzzer x 1; Optional internal 2W speaker x 1
Expansion Slot	M.2 slot x 1

Physical Dimension

Dimensions (W x D x H in mm)	372 x 252 x 326
Weight (N. W. in kg)	5.86

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	M.2 WiFi/BT module
------	--------------------

Attachment Options

POS Monitor	Non-touch TFT USB LCD: 7"/9.7"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display
Attachment	MSR; iButton; RFID; Fingerprint Sensor; Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
* The product information and specifications are subject to change without prior notice.
* Please refer to the website for more attachment options.

POSIFLEX

Certifications



EN20240402V2

Authorized Distributor / Reseller

CDG | Computer Peripheral and Supplies Ltd.

Computer Peripheral and Supplies Ltd.
244 Soi Pattanakarn 53, Pattanakarn, Suanluang, Bangkok 10250 Thailand

f : facebook.com/cps.co.th
t : Tel. 02-7224040 Ext.9
e : sales.dept@cps.co.th
g : www.cps.co.th

f t w y CPS
Other
t : Tel : (66) 0-2322-9535
e : Fax : (66) 0-2322-7990



Powerful yet Thrifty



PS-3616-G2

Best Value Fanless POS Terminal

Crafted with functionality and flexibility in mind, PS-3616-G2 features a 15.6" wide touch screen, fanless technology, and an adjustable base to scale to meet both retailers' and consumers' expectations—all within an affordable, yet attractive and feature-rich terminal.

PS-3616-G2

Specification	PS-3616-G2
Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache
System Memory	DDR4 SO-DIMM x 1, max. 16GB
Storage Device	M.2 connector (SATA Signal Only) x 1
TPM	Yes, TPM 2.0
Power Supply	12V/60W
OS Support	Windows 10 IoT LTSC / Windows 11 IoT LTSC

Display & Touch

LCD	15.6" TFT LCD
Resolution	1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)

I/O & Expansion

Serial Port	4, DB9 x 3 + RJ45 x 1, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable through service window
Standard USB Port	5, USB 3.0 x 2 + USB 2.0 x 2 (on I/O plate) + USB 2.0 x 1 (on the top)
Powered USB Port	Optional 24V x 1 + 12V x 3 via GEN8 base
OTG USB	N/A
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer
PS/2 Port	1, via optional conversion cable through service window
Audio	Buzzer x 1; Optional internal 2W speaker x 1
Expansion Slot	M.2 slot x 1

Physical Dimension

Dimensions (W x D x H in mm)	372 x 252 x 291.4
Weight (N. W. in kg)	4.7

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	M.2 WiFi/BT module
------	--------------------

Attachment Options

POS Monitor	Non-touch TFT USB LCD: 7"/9.7"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display
Attachment	MSR; iButton; RFID; Fingerprint Sensor; Keypad

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
* The product information and specifications are subject to change without prior notice.
* Please refer to the website for more attachment options.

POSIFLEX

Certifications	      	EN20240402V2
----------------	--	--------------

Authorized Distributor / Reseller