

KR-160 Kiosk Passport Reader

The KR-160 is a newly designed, multi-functional document scanner with a removable cover. It is based on OCR technology and compliant with ICAO 9303 standard. It is able to extract data from Passport, Visa, ID card, Driver License and other travel documents. It provides perfect solutions for kiosk and desktop ID authentication.



Multipurpose & Multifunctional

Reads multiple documents with ICAO 9303 doc specification, and non-ICAO 9303 documents such as passport, epassport, visa, ID, eID card, driver license etc.

Fast & Time Saving

Only takes 1 to 2 seconds to process which speeds up a lot queuing time.

Automatic Detection & OCR Processing

Just place the document properly, it will detect and capture the image automatically, free your hands and eliminate human typing error.

Easy to integrate SDK

With detailed API user guide and full SDK, it is easy to integrate the reader into user's own application system and visitor management system.



Specifications

Illumination sources Visible, IR(850nm)

Anti-glare Elimination of glare from holographic anti-counterfeiting film and reflection of light

Image Acquisition Active scan area: 127mm x 88mm | CMOS, 500 Megapixels (2592*1944)

Imaging Color Depth: 24 bits/pixels | Resolution: 500 DPI | Image Format: JPEG, BMP, PNG

Crop for Headshot Cropping of a document headshot image from a general image

OCR Recognition Support extract data and image from ICAO 9303 Standard compliant documents and other

Non-ICAO 9303 Standard compliant document, like ID card, Driver's License, Exit-entry Permit to

HK/Macau, and etc by OCR

Barcode:

1D: Code 128, Code 39, EAN-13, and etc & 2D: PDF417, QR, DataMatrix™, and etc

Scanning speed less than 1 second

Machine Readable Zone ICAO 9303 Standard compliant documents - ID-1, ID-2, ID-3

Non-ICAO 9303 Standard compliant documents issued by China

IP Rating IP50

Data Communication Compatible USB 2.0, USB 3.0, PC/SC

Communication Speed Up to 848kbps

Auto-trigger Automatic detection of a document in a scanning area

Auto-classification Automatic recognition of a ID document type

Status Indicators Four status indicator LEDs (for Power, Ready, Error, and Warning) & customize indicators

Software Complete OCR SDK including DLLs, OCXs, Websocket, and Demo program

Programming Language: VC, VB, C#, Java, etc. Provide OCR SDK for Linux.

Power Input: AC 100~240V 50~60Hz, 0.8A / Output: DC 12V, 2A

Environmental Humidity: 20% to 95% non-condensing | Temperature: Operating: -10°C to 50°C

Storage: -20°C to 50°C

OS compatibility Windows® 2000-SP4, Windows® XP, Windows® Vista, Windows® 7, Windows® 8,

Windows® 10, and Linux®

Hardware Dimension: 193.2*166*104.3mm | Net Weight: 1.30Kg | Gross Weight: 2.11Kg

Warranty 1 year warrany



Computer Peripheral and Supplies Ltd.

