

Interzinc 22 series

Rapid recoat zinc silicate technology

Get faster productivity with a re-coat time of just 4½ hours at 25°C (77°F) and 55% relative humidity.

The Interzinc® 22 series delivers consistently fast re-coating across a choice of 85%, 80%, 77% or 65% minimum zinc content products. The variable zinc levels allow you to tailor your choice of product to meet NORSOK, SSPC Paint 20 or ISO 12944 standards.


- Fast recoat times enhancing shop throughput of coated steel
- Technology allows overcoating in just 4½ hours at 25°C (77°F) and 55% relative humidity
- A range of zinc silicate products with different zinc levels allowing you to select the right product for your needs
- Interzinc® 22 and Interzinc® 2280 products are Norsok M501 compliant allowing offshore use
- Interzinc® 22 zinc product is Class B Slip Coefficient approved for use on slip critical surfaces
- ASTM D520 type II zinc dust supplied as standard, minimizing HSE impact




“The new fast cure Interzinc 22 is the best inorganic zinc silicate we have ever sprayed”

Jason Niles - Shipping, Blast & Paint Supervisor, J&G Steel Corporation, Oklahoma, USA

Re-coat time at 25°C (77°F) and 55% relative humidity



Total application time @ 25°C (77°F) and 55% relative humidity



The Interzinc® 22 series is a group of four products that are all based on the same silicate binder technology as Interzinc® 22, but differ in the amount of zinc dust they have in the dry film. The products are:

- Interzinc® 22 - minimum 85% zinc dust in the dry film
- Interzinc® 2280 - minimum 80% zinc dust in the dry film
- Interzinc® 2277 - minimum 77% zinc dust in the dry film
- Interzinc® 2265 - minimum 65% zinc dust in the dry film

The Interzinc® 22 series is suitable for use with a wide range of high performance systems and topcoats in both maintenance and new construction projects making them ideal for bridges, tanks, pipe work, offshore structures and structural steelwork.

The Interzinc® 22 series can also provide excellent corrosion protection up to temperatures of 540°C (1004°F) when suitably topcoated.

Increased productivity

The technology used in the Interzinc® 22 series results in much faster re-coat times than conventional zinc silicates and can be overcoated in just 4½ hours at 25°C (77°F) and 55% relative humidity. This allows faster throughput of coated steel greatly enhancing productivity.

Case study

Application of Interzinc® 22 to a steel shipping container was carried out at 19°C (66°F) and 58% relative humidity. The fast cure Interzinc® 22 was ready to overcoat in just under five hours allowing a sealer coat and intermediate coat of Intergard® 475HS to be applied in the same day. This meant that the finish coat, Interthane® 990, could be applied the following day, a full 24 hours earlier than if a conventional, slow drying inorganic zinc silicate had been used.



Application of fast cure Interzinc® 22 and tie coat/intermediate coat on day 1



Application of Interthane® 990 finish coat completed on day 2

The standards that the Interzinc® 22 series products comply with

PRODUCT	DESCRIPTION	STANDARDS				
		MINIMUM ZINC CONTENT	NORSOK M501 ¹	ISO 12944 ²	SSPC PAINT 20 LEVEL 1 ³	SSPC PAINT 20 LEVEL 2 ²
Interzinc® 22	85% zinc rich product	✓	✓	✓	✓	✓
Interzinc® 2280	80% zinc rich product based on Interzinc® 22	✓	✓	✗	✓	✓
Interzinc® 2277	77% zinc rich product based on Interzinc® 22	✗	✗	✗	✓	✓
Interzinc® 2265	65% zinc rich product based on Interzinc® 22	✗	✗	✗	✗	✓

www.international-pc.com
pc.communication@akzonobel.com

All trademarks mentioned in this publication are owned by the AkzoNobel group of companies. © Akzo Nobel 2014. AkzoNobel has used its best endeavors to ensure that the information contained in this publication is correct at the time of printing. Please contact your local representative if you have any questions. Unless otherwise agreed by us in writing, any contract to purchase products referred to in this brochure and any advice which we give in connection with the supply of products are subject to our standard conditions of sale.