

CP- UNR-4K2161-V2

16 Ch. Network Video Recorder



Main Features

- Support 16 Channel IP Camera Input
- H.265/H.264 dual codec decoding
- Up to 8MP resolution preview and playback
- Max 160Mbps incoming bandwidth
- Support 1 SATA HDDs up to 6TB, 2 USB ports(2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K2161-V2

16 Ch. Network Video Recorder

Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Record Rate
Video Resolution
Video Recording
Video Display Split
OSD
Bit Rate
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Record Interval
Max User Account
Ethernet
Protocols

Specification

Dual-core embedded processor
Embedded LINUX
16 channel
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.265/H.264
Max 160 Mbps
1920×1080, 1280×1024, 1280×720
8MP @ 15/6MP @ 15/5MP @ 20/4MP @ 20/3MP @ 30/1080P @ 30/ 720P @ 30/ D1&etc.
1/4/8/9/16
Camera title, Time, Camera lock, Motion detection, Recording
16Kbps ~ 20Mbps Per Channel
MD Zones: 396(22×18).
Supports
Supports
iPhone, iPad, Android Phone
1 SATA III ports, up to 6TB Each
Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Manual, Schedule(Main&Sub steam), Regular (Continuous), MD, Stop
Time/Date, MD & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / Network
1 HDMI, 1 VGA, 2 USB Ports(1 Rear USB2.0, 1 Front USB2.0)
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
1 RJ-45 port (10/100/1000Mbps)
HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, SSL, ONVIF 2.4, SDK, CGI

CP- UNR-4K2161-V2

16 Ch. Network Video Recorder

Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

DC12V/2A

<3W (without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm x 224.9mm x 47.6mm

0.8 kg (without HDD)