

# **TURBO Rust Cleaner**

### SECTION 1 – PRODUCT AND COMPANY INDENTIFICATION

PRODUCT NAME	TURBO Rust Cleaner
MANUFACTURER	Turbo Paint, NDW Chemical Co., Ltd.
TELEPHONE	(662) 750 6804
FAX	(662) 312 1707
EMAIL ADDRESS	marketing.ndw@gmail.com
ADDRESS	87/1 Moo 11 Thanasit, Theparak Rd., Bangplee, Samutprakarn 10540 Thailand

# **SECTION 2 – INFORMATION ON INGREDIEANTS**

NAME	CAS No.	UN No.	%	RISK PHRASES
Sodium Thioglycolate	367-51-1	-	15-30	
Potassium Hydroxide Solution (40%)	1310-58-3	-	1-2	
Sodium Benzenesulfonate	68411-30-3	-	3-6	
Sodium Laureth Sulfate	68891-38-3	-	< 1	
RO Water	-	-	50-65	
Fragrance	-	-	< 0.05	
Sodium Dodecyl Poly	9004-82-4	-	3-5	

# **SECTION 3 – HARZARDS IDENTIFICATION**

Inflammable

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful by inhalation and in contact with skin.

#### **SECTION 4 – FIRST AID MEASURES**

Eye ContactFlush with water immediately for 15 minutes. Consult a physician.Skin ContactFlush skin with plenty of water while removing contaminated clothing<br/>and shoes. Launder clothing before reuse. If rash or irritation develops,







# **TURBO Rust Cleaner**

	consult a physician.
Inhalation	Remove to fresh air. Administer oxygen if necessary. Consult a physician
	if symptoms persist or exposure was severe.
Ingestion	If swallowed do not induce vomiting. Seek immediate medical attention.

### SECTION 5 – FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media Recommended: alcohol resistant foam, CO2, powders, water spray.
Recommendations Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

# SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
Spill Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### **SECTION 7 – HANDLING AND STORAGE**

Handling Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty containers. Avoid breathing vapors or spray mist.
Storage Keep away from heat, sparks, open flames and oxidizing agents. Keep containers closed. Store in a cool, dry place with adequate ventilation.







# **TURBO Rust Cleaner**

### **SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

Engineering Measures	Provide forced air ventilation when applying in confined spaces.
<b>Respiratory Protection</b>	Unlikely to be necessary. Use approved chemical filter respirator.
Eyes	Safety glasses or chemical eye goggles are suggested.
Hands	Non-natural, non-butyl rubber gloves are recommended.
Skin	Use protective clothing. Remove contaminated clothing and wash the affected
	with soap and water.

#### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Physical State	Liquid
Color	Milky White
Odor	Low Odor
Specific Gravity	1.00 + - 0.3
Viscosity	-
Solubility in Water	Soluble

# **SECTION 10 – STABILITY AND REACTIVITY**

Stability	Stable under recommended storage and handling conditions (see section 7).		
Hazardous Decomposi	tion Products	carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	
Strong exothermic rea	ctions	oxidizing agents, strong alkalis, strong acids.	

#### **SECTION 11 – TOXICOLOGICAL INFORMATION**

Not Available

**SECTION 12 – ECOLOGICAL INFORMATION** 

Prolonged or repeated contact may cause chronic dermatitis. Appreciable evaporation to air is expected in the environment.







### **TURBO Rust Cleaner**

#### **SECTION 13 – DISPOSAL CONSIDERATIONS**

#### Method of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14 – TRANSPORT INFORMATION**

Proper shipping name	Thioglycolic Acid Sodium Salt Solution
Packing Group	III
Hazard Class	IATA: 9
UN No.	IATA: 3335

### **SECTION 15 – REGULATORY INFORMATION**

Highly flammable Harmful by inhalation, in contact with skin and if swallowed Irritating to eye and skin Keep out of reach of children Keep away from sources of ignition – No Smoking Do not breathe gas/fumes/vapour/spray Avoid contact with skin and eyes Wear suitable protective clothing, gloves and eye/face protection

### **SECTION 16 – OTHER INFORMATION**

This document could not be used for certifying the quality of the product.

This document presents the information of the product and to be used for safety only.

The above information and data given here is based on test, experiences that are considered reliable and believed to be accurate. For more information,

Remark





Page 4 of 5



# **TURBO Rust Cleaner**

please contact R&D department of NDW Co., Ltd.



