

TOSHIBA

Lighting products and gears

PRODUCTS CATALOG



TOSHIBA

LED Circular Lamp






LED Circular Lamp


Take away the original starter to replace the traditional fluorescent circular lamp directly, and don't need to take away the original magnetic ballast. Furthermore, can be connected to the main supply which same FCL socket (G10Q).

DIMENSION



(mm) G10Q

EQUIVALENT



Compare to conventional fixture with fluorescent lamp

ENERGY SAVING



Non-dimmable



TIS 1955-2551 TTLC



Eye Safety IEC 62471



1kV Surge protection

Product code	Voltage (Vac)	Rated Wattage (W)	Luminous Flux (lm)	Efficacy (lm/W)	Colour Temperature	Color Rendering Index (Ra)	Power Factor	Beam Angle	Lifespan (Hrs.)
RLDC9XC2065AQTH1	220-240	20	2200	110	6500K	80	≥0.5	130°	30,000

Operation temperature : -20°C to 40°C

Thai Toshiba Lighting Co., Ltd.

144 Moo 5 Bangkadi Industrial Park, Tivanon Road, T.Bangkadi, A.Muang, Pathumthani 12000, Thailand
Tel.+66 (0)2 501-1425-9 Fax. +66-2501-1431